

JBF-AS-4X5MP-DOME

4 × 5MP Multi-Sensor No-Splicing Panoramic Dome Network Camera



Launched by JBF Technology, is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, provides precise, reliable and comprehensive AI solutions for verticals.

Series Overview

The non-splicing camera can adjust each lens to realize 360° surveillance, which can be used in the scenes with multiple cameras, and is easy to install. Stereo vision camera has the functions such as deep detection and behavior analysis.

Functions

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, JBF smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

Perimeter Protection

With deep learning algorithm, JBF Perimeter Protection technology can recognize human and vehicle accurately. In restricted area (such as pedestrian area and vehicle area), the false alarms of intelligent detection based on target type (such as tripwire, intrusion, fast moving, parking detection, loitering detection and gathering detection) are largely reduced.

Face Detection

JBF Face Detection technology can detect the face in the image. With deep learning algorithm, the technology supports detecting, tracking, capturing and selecting the best face image, and then outputs face snapshot.



- 4 × 5MP 1/2.7" CMOS image sensor, low illuminance, high image definition
- 4-channel stream output, and each channel can output max. 5MP (2592 × 1944) @25/30 fps
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Support 4-channel 120 dB WDR
- The intelligent functions of 4 channels can be enabled at the same time
- Intelligent detection: Tripwire, intrusion, fast moving (the three functions support the classification and accurate detection of vehicle and human), abandoned object, missing object, loitering detection, people gathering, parking detection, and face detection
- FlexStream: The 4 channels of images can be viewed in a defined channel with 1 channel stream. That is, the multiple images can be displayed in 1 channel.
- Web5.0 interface design, which is friendly to users, and easy for operation
- Built-in efficient IR LED illuminator, and the max. illumination distance is 30 m
- Recording Failover
- Video Analysis
- IP Address locking system, after several (customizable) number of wrong access
- User access log cannot be deleted by reset
- Request function to create or change password at first login
- Micro SD memory (encryption AES128 or AES256)
- Alarm: 3 in, 2 out; audio: 1 in, 1 out; 485; supports max. 256 G Micro SD card
- 12V DC/POE power supply; 12V power output, and max. current 165mA; easy for installation
- IP67, IK10 protection

One IP Address for Multiple Streams

With one IP address, JBF multi-sensor camera can display multiple images. The camera can do multi-image monitoring through software platform or NVR.

Cyber Security

JBF network cameras employ a series of security technologies, including security authentication and authorization, access control protocols, trusted protection, encrypted transmission and encrypted storage. These technologies improve the camera's defense against external cyber threats and prevent malicious programs from comprising the device.

WDR

With advanced Wide Dynamic Range 120dB WDR technology, JBF network camera provides clear details in the environment of strong brightness contrast. The bright and dark area can get clear video even in high brightness environment or with backlight shadow.

JBF-AS-4X5MP-DOME

Protection (IP67, IK10, wide voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can works normal after soaking in 1 m deep water for 30 minutes.

IK10: The enclosure can stand the punch more than 5 times from a 5 kg hammer falling from a height of 40 cm (Impact energy is 20J).

Wide voltage: The camera allows ±30% (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

Technical Specification

Camera	
Image Sensor	1/2.7"5Megapixel progressive CMOS
Max. Resolution	2592 (H) × 1944 (V)
ROM	32 GB
RAM	4 GB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Min. Illumination	0.005 Lux@F1.7(Color,30IRE) 0.0005 Lux@F1.7(B/W,30IRE) 0 lux (Illuminator on)
S/N Ratio	> 56 dB
Illumination Distance	30 m (98.4 ft) (IR LED)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	8 (IR LED)
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–80° Rotation: 0°–355°

Lens

Lens Type		Motorized vari-focal			
Mount Type		φ14			
Focal Length		2.8 mm–12 mm			
Max. Aperture		F1.7			
Field of View		Horizontal: 100°–36° Vertical: 74°–27° Diagonal: 133°–45°			
Iris Type		Fixed			
Close Focus Distance		0.8 m (2.6 ft)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	66 m (216.5 ft)	26.4 m (86.6 ft)	13.2 m (43.3 ft)	6.6 m (21.7ft)
	T	140.4 m (460.6 ft)	56.1 m (184.1 ft)	28 m (91.9 ft)	14 m (45.9 ft)

Smart Event

IVS	Abandoned object; missing object
-----	----------------------------------

Professional, intelligent

IVS (Perimeter Protection)	Tripwire; intrusion; fast moving (the three functions support the classification and accurate detection of vehicle and human); loitering detection; people gathering; parking detection
Face Detection	Face detection; track; optimization; snapshot; report high quality picture; face enhancement; face exposure; face attribute extract, 6 attributes and 8 expressions: Gender, age, glasses, expressions (anger, calm, happiness, sadness, disgust, surprise, confusion and fear), mask, beard; face matting setting: face, single inch photo; three snapshot methods: real-time snapshot, optimization snapshot, quality priority; face angle filter; optimization time setting
Intelligent Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos.

Video

Video Compression	H.265; H.264; H.264H; H.264B; MJPEG (only supported by the sub stream)
Smart Codec	Smart H.265+/Smart H.264+
Video Frame Rate	Single Stream: Main stream: 5MP (1–25/30 fps) Sub stream: D1 (1–25/30 fps) Third stream: 2MP (1–25/30 fps) FlexStream: Main stream: 2MP (1–25/30 fps) Sub stream: D1 (1–25/30 fps) Third stream: 8MP (1–25/30 fps)
Stream Capability	3 streams
Resolution	Single Stream: 5M(2592×1944); 4M(2688×1520); 3M(2048×1536);2M(1920×1080);720P(1280×720); D1(704× 576/704×480);CIF(352×288/352×240) FlexStream:8M(3296×2472);5M(2592×1944); 2M(1600×1200);1.3M(1280×960); D1(704× 576/704×480);CIF(352×288/352×240)
Bit Rate Control	CBR/VBR
Video Bit Rate	H.264: 3 kbps–19456 kbps H.265: 3 kbps–19456 kbps
Day/Night	Auto (ICR)/Color/B/W
BLC	Yes
HLC	Yes
WDR	4 × 120 dB
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom
Gain Control	Auto/Manual
Noise Reduction	3D NR
Motion Detection	OFF/ON (4 areas, rectangular)
Region of Interest (RoI)	Yes (4 areas)
Smart Illumination	Yes
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 1080p resolution and lower)
Mirror	Yes
Privacy Masking	4 areas

JBF-AS-4X5MP-DOME

Audio

Audio Compression	G.711a; G.711Mu; PCM; G.726; G.723
-------------------	------------------------------------

Alarm

Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; intrusion; tripwire; fast moving; abandoned object; missing object; loitering detection; people gathering; parking detection; scene changing; audio detection; voltage detection; defocus detection; external alarm; face detection; safety exception; voltage detection
-------------	--

Network

Network	RJ-45 (10/100/1000 Base-T)
SDK and API	Yes
Cyber Security	Video encryption; firmware encryption; configuration encryption; Digest; WSSE; account lockout; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot; trusted execution; trusted upgrade
Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
ONVIF	Version 21.06 rev. 6999, Profile S, Profile T, Profile G
Storage	FTP; SFTP; Micro SD card (support max. 256 G); NAS
Browser	IE: IE9 and later Chrome: 41.0 and later No-plug version: Safari and edge
Management Software	Smart PSS; DSS
Mobile Phone	IOS; Android

Certification

Certification	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
---------------	--

Port

RS-485	1 (baud rate range: 1200 bps–115200 bps)
Audio Input	1 channel (RCA port)
Audio Output	1 channel (RCA port)
Alarm Input	3 channel in: 5mA 3V–5V DC
Alarm Output	2 channel out: 300mA 12V DC

Power

Power Supply	12V DC/POE(802.3at)
Power Consumption	Basic power consumption: 8.1W (12V DC); 9W (PoE) Max. power consumption (ICR + IR intensity): 21.5W (12V DC); 22.2W (POE+)

Environment

Operating Conditions	–30°C to +60°C (–22°F to +140°F)/Less than 95% RH
Storage Conditions	–30°C to +60°C (–22°F to +140°F)
Protection Grade	IP67; IK10

Structure

Casing	Metal + Plastic
Dimensions	286.1 mm × 111.3 mm (11.3" × 4.4")
Net Weight	2.75 kg (8.9 lb)
Gross Weight	4.5 kg (11.0 lb)

Accessories

Optional



JBF-AS-FPB3W Wall Mount Bracket




JBF-AS-FPB3C Ceiling Mount Bracket



JBF-AS-FPASG Mount Adapter



JBF-AS-FPA08 Mount Adapter



Dimensions (mm [inch])

